

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD  
CENTRAL VALLEY REGION

MONITORING AND REPORTING PROGRAM NO. \_\_\_\_\_  
FOR  
H.M. HOLLOWAY, INC.  
FOR  
H.M. HOLLOWAY SURFACE MINE LANDFILL PROJECT  
KERN COUNTY

The Discharger shall comply with this Monitoring and Reporting Program (MRP), with Title 27, California Code of Regulations, Section 20005, et seq. (hereafter Title 27), and with the *Standard Provisions and Reporting Requirements for Waste Discharge Requirements for Nonhazardous Solid Waste Discharges Regulated by Title 27 and/or Subtitle D (27 CCR §20005 et seq. and 40 CFR 258)*, dated April 2000, as ordered by Waste Discharge Requirements Order No. \_\_\_\_\_.

**A. REQUIRED MONITORING REPORTS**

1. Groundwater Monitoring (Section D.1)
2. Unsaturated Zone Monitoring (Section D.2)
3. Leachate Monitoring (Section D.3)
4. Facility Monitoring (Section D.4)
5. Annual Monitoring Summary Report (Section E.5.)
6. Response to a Release (Standard Provisions and Reporting Requirements)

**B. REPORTING**

H.M. Holloway, Inc. (hereafter Discharger), shall report monitoring data and information as required in this MRP and as required in Order \_\_\_\_\_ and the Standard Provisions and Reporting Requirements. Reports which do not comply with the required format will be **REJECTED** and the Discharger shall be deemed to be in noncompliance with the waste discharge requirements. In reporting the monitoring data required by this program, the Discharger shall arrange the data in tabular form so that the date, the constituents, the concentrations, and the units are readily discernible. The data shall be summarized in such a manner so as to illustrate clearly the compliance with waste discharge requirements or the lack thereof. Data shall also be submitted in a digital format acceptable to the Executive Officer. Each monitoring report shall include a compliance evaluation summary as specified in E. Reporting Requirements, below.

TENTATIVE

### Report Due Dates

Field and laboratory tests shall be reported in each monitoring report. Monthly, quarterly, semiannual, and annual monitoring reports shall be submitted to the Central Valley Water Board in accordance with the following schedule for the calendar period in which samples were taken or observations made.

<u>Sampling Frequency</u>	<u>Reporting Frequency</u>	<u>Reporting Periods End</u>	<u>Report Date Due</u>
Monthly	Semiannually	Last Day of Month	<b>by Semiannual Schedule</b>
Quarterly	Semiannually	31 March	<b>31 July</b>
		30 June	<b>31 July</b>
		30 September	<b>31 January</b>
		31 December	<b>31 January</b>
Semiannually	Semiannually	30 June	<b>31 July</b>
		31 December	<b>31 January</b>
Annually	Annually	31 December	<b>31 January</b>
5-Year	Every 5 years	31 December	<b>31 January</b>

The Discharger shall submit an **Annual Monitoring Summary Report** covering the previous monitoring year. The annual report shall contain the information specified in E. Reporting Requirements, below, and a discussion of compliance with the waste discharge requirements and the Water Quality Protection Standard.

The results of **all monitoring** conducted at the site shall be reported to the Central Valley Water Board in accordance with the reporting schedule above for the calendar period in which samples were taken or observations made.

## C. WATER QUALITY PROTECTION STANDARD AND COMPLIANCE PERIOD

### 1. Constituents of Concern

The constituents of concern include all the waste constituents, their reaction products, and hazardous constituents that are reasonably expected to be in or derived from waste contained in the Unit. The constituents of concern for all Units at the facility are those listed in Tables I through V for the specified monitored medium. The Discharger shall monitor all constituents of concern every five years.

a. **Monitoring Parameters**

Monitoring parameters are constituents of concern that are the waste constituents, reaction products, hazardous constituents, and physical parameters that provide a reliable indication of a release from a Unit. The monitoring parameters for all Units are those listed in Tables I through IV for the specified monitored medium.

**2. Concentration Limits**

For a naturally occurring constituent of concern, the concentration limit for each constituent of concern shall be determined as follows:

- a. By calculation in accordance with a statistical method pursuant to §20415 of Title 27(e)(8); or
- b. By an alternate statistical method meeting the requirements of §20415(e)(8)(E) of Title 27.

**3. Point of Compliance**

The point of compliance for the water standard at each Unit is a vertical surface located at the hydraulically downgradient limit of the Unit that extends through the uppermost aquifer underlying the Unit.

**4. Compliance Period**

The compliance period for each Unit shall be the number of years equal to the active life of the Unit plus the closure period. The compliance period is the minimum period during which the Discharger shall conduct a water quality monitoring program subsequent to a release from the Unit. The compliance period shall begin anew each time the Discharger initiates an evaluation monitoring program.

**D. MONITORING**

The Discharger shall comply with the detection monitoring program provisions of Title 27 for groundwater, and the unsaturated zone, in accordance with Detection Monitoring Specification E.1 and E.4 of Waste Discharge Requirements, Order No. \_\_\_\_\_. All monitoring shall be conducted in accordance with a Sample Collection and Analysis Plan, which includes quality assurance/quality control standards, that is acceptable to the Executive Officer.

All monitoring wells established for the detection monitoring program shall constitute the monitoring points for the groundwater Water Quality Protection Standard. All detection monitoring program groundwater monitoring wells, and unsaturated zone monitoring devices, shall be sampled and analyzed for monitoring parameters and constituents of concern as indicated and listed in Tables I through V.

Method detection limits and practical quantitation limits shall be reported. All peaks shall be reported, including those which cannot be quantified and/or specifically identified. Metals shall be analyzed in accordance with the methods listed in Table V.

The Discharger may, with the approval of the Executive Officer, use alternative analytical test methods, including new USEPA approved methods, provided the methods have method detection limits equal to or lower than the analytical methods specified in this Monitoring and Reporting Program.

## **1. Groundwater**

The Discharger shall operate and maintain a groundwater detection monitoring system that complies with the applicable provisions of §20415 and §20420 of Title 27 in accordance with a Detection Monitoring Program approved by the Executive Officer. The detection monitoring system shall be certified by a California-licensed professional civil engineer or geologist as meeting the requirements of Title 27. The Discharger shall collect, preserve, and transport groundwater samples in accordance with the approved Sample Collection and Analysis Plan.

The Discharger shall determine the groundwater flow rate and direction, if possible, in the uppermost aquifer and in any zones of perched water and in any additional zone of saturation monitored pursuant to this Monitoring and Reporting Program, and report the results semiannually, including the times of highest and lowest elevations of the water levels in the wells.

Hydrographs of each well shall be submitted showing the elevation of groundwater with respect to the elevations of the top and bottom of the screened interval and the elevation of the pump intake. Hydrographs of each well shall be prepared quarterly and submitted annually.

Groundwater samples shall be collected from all monitoring wells that are part of the approved groundwater monitoring system. Samples shall be collected and analyzed for the monitoring parameters in accordance with the methods and frequency specified in Table I.

The monitoring parameters shall also be evaluated each reporting period with regards to the cation/anion balance, and the results shall be graphically

presented using a Stiff diagram, a Piper graph, or a Schoeller plot. Samples for the constituents of concern specified in Table I shall be collected and analyzed in accordance with the methods listed in Table IV every five years.

## **2. Unsaturated Zone Monitoring**

The Discharger shall operate and maintain an unsaturated zone detection monitoring system that complies with the applicable provision of Section 20415 and 20420 of Title 27 in accordance with an approved Detection Monitoring Program. The Discharger shall collect, preserve, and transport samples in accordance with the quality assurance/quality control standards contained in the approved Sample Collection and Analysis Plan.

Unsaturated zone samples shall be collected from the monitoring device(s) of the approved unsaturated zone monitoring system. The collected samples shall be analyzed for the listed constituents in accordance with the methods and frequency specified in Table II. All monitoring parameters shall be graphed so as to show historical trends at each monitoring point. Samples for the constituents of concern specified in Table II shall be collected and analyzed in accordance with the methods listed in Table IV every five years.

Unsaturated zone monitoring reports shall be included with the corresponding semiannual groundwater monitoring and shall include an evaluation of potential impacts of the facility on the unsaturated zone and compliance with the Water Quality Protection Standard.

## **3. Leachate Monitoring**

All leachate collection and removal system sumps shall be inspected monthly for leachate generation. Upon detection of leachate in a previously dry leachate collection and removal system, leachate shall be sampled within two days and analyzed for the constituents listed in Table III. Leachate shall then be sampled and analyzed annually during the fourth quarter thereafter, with a retest during the following second quarter if constituents are detected that have not been previously detected. Leachate samples shall be collected and analyzed for the listed constituents in accordance with the methods and frequency specified in Table III. The constituents of concern list shall include all constituents listed in Table V. The quantity of leachate pumped from each sump shall be measured and reported monthly as Leachate Flow Rate (in gallons).

Leachate which seeps to the surface from the Unit shall be sampled and analyzed for the constituents listed in Table III upon detection. The quantity of leachate shall be *estimated* and reported as Leachate Flow Rate (in gallons/day).

#### 4. Facility Monitoring

##### a. Facility Inspection

Annually, prior to the anticipated rainy season, but no later than **30 September**, the Discharger shall conduct an inspection of the facility. The inspection shall assess damage to the drainage control system, groundwater monitoring equipment (including wells, etc.), and shall include the Standard Observations contained in Section E.3.f., below. Any necessary construction, maintenance, or repairs shall be completed by **31 October**. By **15 November** of each year, the Discharger shall submit an annual report describing the results of the inspection and the repair measures implemented, including photographs of the problem and the repairs.

##### b. Storm Events

The Discharger shall inspect all precipitation, diversion, and drainage facilities for damage **within 7 days** following *major storm events* (i.e., a storm that causes continuous runoff for at least one hour). Necessary repairs shall be completed **within 30 days** of the inspection. The Discharger shall report any flooding, unpermitted discharge of waste off-site, equipment failure, slope failure, or other change in site conditions that could impair the integrity of waste containment facilities and subsequent repairs within 45 days of completion of the repairs, including photographs of the problem and the repairs. Minor damage and subsequent repairs shall be reported in the next self-monitoring report.

#### E. REPORTING REQUIREMENTS

1. The Discharger shall retain records of all monitoring information, including all calibration and maintenance records, all original strip chart recordings of continuous monitoring instrumentation, copies of all reports required by this Order, and records of all data used to complete the application for this Order. Records shall be maintained throughout the life of the facility including the postclosure period.

Such legible records shall show the following for each sample:

- a. Sample identification and the monitoring point or background monitoring point from which it was taken, along with the identity of the individual who obtained the sample;
- b. Date, time, and manner of sampling;

- c. Date and time that analyses were started and completed, and the name of the personnel and laboratory performing each analysis;
  - d. Complete procedure used, including method of preserving the sample, and the identity and volumes of reagents used;
  - e. Calculation of results; and
  - f. Results of analyses, and the MDL and PQL for each analysis.
2. A transmittal letter explaining the essential points shall accompany each report. At a minimum, the transmittal letter shall identify any violations found since the last report was submitted, and if the violations were corrected. If no violations have occurred since the last submittal, this shall be stated in the transmittal letter. The transmittal letter shall also state that a discussion of any violations found since the last report was submitted, and a description of the actions taken or planned for correcting those violations, including any references to previously submitted time schedules, is contained in the accompanying report.
3. Each monitoring report shall include a compliance evaluation summary. The summary shall contain at least:
  - a. For each monitoring point and background monitoring point addressed by the report, a description of:
    - 1) The time of water level measurement;
    - 2) The type of pump - or other device - used for purging and the elevation of the pump intake relative to the elevation of the screened interval;
    - 3) The method of purging (the pumping rate; the equipment and methods used to monitor field pH, temperature, and conductivity during purging; the calibration of the field equipment; results of the pH, temperature, conductivity, and turbidity testing; and the method of disposing of the purge water) to remove all portions of the water that was in the well bore while the sample was being taken;
    - 4) The type of pump - or other device - used for sampling, if different than the pump or device used for purging; and
    - 5) A statement that the sampling procedure was conducted in accordance with the approved Sampling and Analysis Plan approved by the Executive Officer.
  - b. A map or aerial photograph showing the locations of observation stations, monitoring points, and background monitoring points.

- c. For each groundwater body, a description and graphical presentation of the gradient and direction of groundwater flow under/around the Unit, and the groundwater flow rate, based upon water level elevations taken prior to the collection of the water quality data submitted in the report.
  - d. Laboratory statements of results of all analyses evaluating compliance with requirements.
  - e. An evaluation of the effectiveness of the leachate monitoring and control facilities, and of the run-off/run-on control facilities.
  - f. A summary and certification of completion of all **Standard Observations** for the Unit, for the perimeter of the Unit. Standard observations for the closed landfill unit shall be conducted **monthly** during the wet season (1 October to 30 April) and **quarterly** during the dry season (1 May to 30 September). The Standard Observations shall include:
    - 1) For the Unit:
      - a) Evidence of ponded water at any point on the facility (show affected area on map);
      - b) Evidence of erosion and/or of day-lighted refuse.
    - 2) Along the perimeter of the Unit:
      - a) Evidence of liquid leaving or entering the Unit, estimated size of affected area, and flow rate (show affected area on map);
      - b) Evidence of erosion and/or of day-lighted refuse.
4. The Discharger shall report by telephone any seepage from the disposal area **immediately** after it is discovered. A written report shall be filed with the Central Valley Water Board **within seven days**, containing at least the following information:
- a. A map showing the location(s) of seepage;
  - b. An estimate of the flow rate;
  - c. A description of the nature of the discharge (e.g., all pertinent observations and analyses);
  - d. Verification that samples have been submitted for analyses of the Monitoring Parameters and Constituents of Concern listed in Table III of this MRP, and an estimated date that the results will be submitted to the Central Valley Water Board; and

- e. Corrective measures underway or proposed, and corresponding time schedule.
5. The Discharger shall submit an **Annual Monitoring Summary Report** to the Central Valley Water Board covering the reporting period of the previous monitoring year. This report shall contain:
- a. All monitoring parameters and constituents of concern shall be graphed so as to show historical trends at each monitoring point and background monitoring point, for all samples taken within at least the previous five calendar years. Each such graph shall plot the concentration of one or more constituents for the period of record for a given monitoring point or background monitoring point, at a scale appropriate to show trends or variations in water quality. The graphs shall plot each datum, rather than plotting mean values. For any given constituent or parameter, the scale for background plots shall be the same as that used to plot downgradient data. Graphical analysis of monitoring data may be used to provide significant evidence of a release.
  - b. All historical monitoring data, including data for the previous year, shall be submitted in tabular form as well as in a digital file format. The Central Valley Water Board regards the submittal of data in hard copy and in digital format as "...the form necessary for..." statistical analysis [Section 20420(h) of Title 27], in that this facilitates periodic review by the Central Valley Water Board.
  - c. A comprehensive discussion of the compliance record, and the result of any corrective actions taken or planned which may be needed to bring the Discharger into full compliance with the waste discharge requirements.
  - d. A written summary of the monitoring results, indicating any changes made or observed since the previous annual report.

The Discharger shall implement the above monitoring program on the effective date of this Program.

Ordered by: \_\_\_\_\_  
PAMELA C. CREEDON, Executive Officer

\_\_\_\_\_  
(Date)

**TABLE I**  
**GROUNDWATER DETECTION MONITORING PROGRAM**

<u>Parameter</u>	<u>Units</u>	<u>Frequency</u>
<b>Field Parameters</b>		
Groundwater Elevation	Ft. & hundredths, M.S.L. <sup>1</sup>	Quarterly
Temperature	°C <sup>2</sup>	Semiannually
Electrical Conductivity	µmhos/cm <sup>3</sup>	Semiannually
pH	pH units	Semiannually
Turbidity	NTU <sup>4</sup>	Semiannually
<b>Monitoring Parameters</b>		
Total Dissolved Solids (TDS)	mg/L <sup>5</sup>	Semiannually
Nitrate (NO <sub>3</sub> )	mg/L	Semiannually
Nitrate as Nitrogen (NO <sub>3</sub> -N)	mg/L	Semiannually
Nitrite (NO <sub>2</sub> -N)	mg/L	Semiannually
Total Kjeldahl Nitrogen	mg/L	Semiannually
Total Nitrogen	mg/L	Semiannually
Ammonia (NH <sub>3</sub> -N)	mg/L	Semiannually
Chloride	mg/L	Semiannually
Carbonate	mg/L	Semiannually
Bicarbonate	mg/L	Semiannually
Phosphorous	mg/L	Semiannually
Sulfate	mg/L	Semiannually
Calcium	mg/L	Semiannually
Magnesium	mg/L	Semiannually
Potassium	mg/L	Semiannually
Sodium	mg/L	Semiannually
Volatile Organic Compounds (USEPA Method 8260, see Table IV)	µg/L <sup>6</sup>	Semiannually

**TABLE I**  
**GROUNDWATER DETECTION MONITORING PROGRAM**  
**(continued)**

**Constituents of Concern (see Table V)**

Total Organic Carbon	mg/L	Every 5 years
Inorganics (dissolved)	mg/L	Every 5 years
Volatile Organic Compounds (USEPA Method 8260, extended list)	µg/L	Every 5 years
Semi-Volatile Organic Compounds (USEPA Method 8270)	µg/L	Every 5 years
Chlorophenoxy Herbicides (USEPA Method 8151)	µg/L	Every 5 years
Organophosphorus Compounds (USEPA Method 8141)	µg/L	Every 5 years

- 
1. Feet and hundredths of a foot above mean sea level.
  2. Degrees Celsius.
  3. Micromhos per centimeter.
  4. Nephelometric turbidity units.
  5. Milligrams per liter.
  6. Micrograms per liter.

**TABLE II**  
**UNSATURATED ZONE MONITORING**

<u>Parameter</u>	<u>Units</u>	<u>Frequency</u>
<b>Field Parameters</b>		
Electrical Conductivity	µmhos/cm <sup>1</sup>	Semiannual
pH	pH units	Semiannual
<b>Monitoring Parameters</b>		
Total Dissolved Solids (TDS)	mg/L <sup>2</sup>	Semiannual
Chloride	mg/L	Semiannual
Carbonate	mg/L	Semiannual
Bicarbonate	mg/L	Semiannual
Nitrate - Nitrogen	mg/L	Semiannual
Sulfate	mg/L	Semiannual
Calcium	mg/L	Semiannual
Magnesium	mg/L	Semiannual
Potassium	mg/L	Semiannual
Sodium	mg/L	Semiannual
Volatile Organic Compounds (USEPA Method 8260, see Table V)	µg/L	Semiannual
<b>Constituents of Concern (see Table VI)</b>		
Total Organic Carbon	mg/L	5 years
Inorganics (dissolved)	mg/L	5 years
Volatile Organic Compounds (USEPA Method 8260, extended list)	µg/L <sup>3</sup>	5 years
Semi-Volatile Organic Compounds (USEPA Method 8270)	µg/L	5 years
Chlorophenoxy Herbicides (USEPA Method 8150)	µg/L	5 years
Organophosphorus Compounds (USEPA Method 8141)	µg/L	5 years

- 
1. Micromhos per centimeter.
  2. Milligrams per liter.
  3. Micrograms per liter.

**TABLE III**  
**LEACHATE DETECTION MONITORING PROGRAM**

<u>Parameter</u>	<u>Units</u>	<u>Frequency</u>
<b>Field Parameters</b>		
Total Flow	Gallons	Monthly
Flow Rate	Gallons/Day	Monthly
Electrical Conductivity	µmhos/cm <sup>1</sup>	Annually
pH	pH units	Annually
<b>Monitoring Parameters</b>		
Total Dissolved Solids (TDS)	mg/L <sup>2</sup>	Annually
Chloride	mg/L	Annually
Carbonate	mg/L	Annually
Bicarbonate	mg/L	Annually
Nitrate - Nitrogen	mg/L	Annually
Sulfate	mg/L	Annually
Calcium	mg/L	Annually
Magnesium	mg/L	Annually
Potassium	mg/L	Annually
Sodium	mg/L	Annually
Volatile Organic Compounds (USEPA Method 8260, see Table V)	µg/L <sup>3</sup>	Annually
<b>Constituents of Concern (see Table VI)</b>		
Total Organic Carbon	mg/L	5 years
Inorganics (dissolved)	mg/L	5 years
Volatile Organic Compounds (USEPA Method 8260, extended list)	µg/L	5 years
Semi-Volatile Organic Compounds (USEPA Method 8270)	µg/L	5 years
Chlorophenoxy Herbicides (USEPA Method 8150)	µg/L	5 years
Organophosphorus Compounds (USEPA Method 8141)	µg/L	5 years

- 
1. Micromhos per centimeter.
  2. Milligrams per liter.
  3. Micrograms per liter.

**TABLE IV**  
**MONITORING PARAMETERS FOR DETECTION MONITORING**

**Surrogates for Metallic Constituents:**

pH  
Total Dissolved Solids  
Electrical Conductivity  
Chloride  
Sulfate  
Nitrate nitrogen

**Constituents included in VOC:**

**USEPA Method 8260**

Acetone  
Acrylonitrile  
Benzene  
Bromochloromethane  
Bromodichloromethane  
Bromoform (Tribromomethane)  
Carbon disulfide  
Carbon tetrachloride  
Chlorobenzene  
Chloroethane (Ethyl chloride)  
Chloroform (Trichloromethane)  
Dibromochloromethane (Chlorodibromomethane)  
1,2-Dibromo-3-chloropropane (DBCP)  
1,2-Dibromoethane (Ethylene dibromide; EDB)  
o-Dichlorobenzene (1,2-Dichlorobenzene)  
m-Dichlorobenzene (1,3-Dichlorobenzene)  
p-Dichlorobenzene (1,4-Dichlorobenzene)  
trans-1,4-Dichloro-2-butene  
Dichlorodifluoromethane (CFC-12)  
1,1-Dichloroethane (Ethylidene chloride)  
1,2-Dichloroethane (Ethylene dichloride)  
1,1 -Dichloroethylene (1,1 -Dichloroethene; Vinylidene chloride)  
cis- 1,2-Dichloroethylene (cis- 1,2-Dichloroethene)  
trans-1,2-Dichloroethylene (trans-1,2-Dichloroethene)  
1,2-Dichloropropane (Propylene dichloride)  
cis- 1,3-Dichloropropene  
trans- 1,3-Dichloropropene  
Di-isopropylether (DIPE)  
Ethanol  
Ethyltertiary butyl ether  
Ethylbenzene  
2-Hexanone (Methyl butyl ketone)  
Hexachlorobutadiene

**TABLE IV**  
**MONITORING PARAMETERS FOR DETECTION MONITORING**  
**Continued**

Hexachloroethane  
Methyl bromide (Bromomethene)  
Methyl chloride (Chloromethane)  
Methylene bromide (Dibromomethane)  
Methylene chloride (Dichloromethane)  
Methyl ethyl ketone (MEK: 2-Butanone)  
Methyl iodide (Iodomethane)  
Methyl t-butyl ether  
4-Methyl-2-pentanone (Methyl isobutylketone)  
Naphthalene  
Styrene  
Tertiary amyl methyl ether  
Tertiary butyl alcohol  
1,1,1,2-Tetrachloroethane  
1,1,2,2-Tetrachloroethane  
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene)  
Toluene  
1,2,4-Trichlorobenzene  
1,1,1-Trichloroethane (Methylchloroform)  
1,1,2-Trichloroethane  
Trichloroethylene (Trichloroethene)  
Trichlorofluoromethane (CFC- 11)  
1,2,3-Trichloropropane  
Vinyl acetate  
Vinyl chloride  
Xylenes

**TABLE V**  
**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

<b><u>Inorganics (dissolved):</u></b>	<b><u>USEPA Method</u></b>
Aluminum	6010
Antimony	7041
Barium	6010
Beryllium	6010
Cadmium	6010
Chromium	6010
Cobalt	6010
Copper	6010
Silver	6010
Tin	200.8
Vanadium	6010
Zinc	6010
Iron	6010
Manganese	6010
Arsenic	200.8
Lead	200.8
Mercury	7470
Nickel	6010
Selenium	200.8
Thallium	200.8
Cyanide	E335.4
Sulfide	376.2

**Volatile Organic Compounds:**

**USEPA Method 8260**

Acetone  
 Acetonitrile (Methyl cyanide)  
 Acrolein  
 Acrylonitrile  
 Allyl chloride (3-Chloropropene)  
 Benzene  
 Bromochloromethane (Chlorobromomethane)  
 Bromodichloromethane (Dibromochloromethane)  
 Bromoform (Tribromomethane)  
 Carbon disulfide  
 Carbon tetrachloride  
 Chlorobenzene  
 Chloroethane (Ethyl chloride)  
 Chloroform (Trichloromethane)  
 Chloroprene  
 Dibromochloromethane (Chlorodibromomethane)

**TABLE V**

**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

1,2-Dibromo-3-chloropropane (DBCP)  
1,2-Dibromoethane (Ethylene dibromide; EDB)  
o-Dichlorobenzene (1,2-Dichlorobenzene)  
m-Dichlorobenzene (1,3-Dichlorobenzene)  
p-Dichlorobenzene (1,4-Dichlorobenzene)  
trans- 1,4-Dichloro-2-butene  
Dichlorodifluoromethane (CFC 12)  
1,1 -Dichloroethane (Ethylidene chloride)  
1,2-Dichloroethane (Ethylene dichloride)  
1,1 -Dichloroethylene (1, 1-Dichloroethene; Vinylidene chloride)  
cis- 1,2-Dichloroethylene (cis- 1,2-Dichloroethene)  
trans- 1,2-Dichloroethylene (trans- 1,2-Dichloroethene)  
1,2-Dichloropropane (Propylene dichloride)  
1,3-Dichloropropane (Trimethylene dichloride)  
2,2-Dichloropropane (Isopropylidene chloride)  
1,1 -Dichloropropene  
cis- 1,3-Dichloropropene  
trans- 1,3-Dichloropropene  
Di-isopropylether (DIPE)  
Ethanol  
Ethyltertiary butyl ether  
Ethylbenzene  
Ethyl methacrylate  
Hexachlorobutadiene  
Hexachloroethane  
2-Hexanone (Methyl butyl ketone)  
Isobutyl alcohol  
Methacrylonitrile  
Methyl bromide (Bromomethane)  
Methyl chloride (Chloromethane)  
Methyl ethyl ketone (MEK; 2-Butanone)  
Methyl iodide (Iodomethane)  
Methyl t-butyl ether  
Methyl methacrylate  
4-Methyl-2-pentanone (Methyl isobutyl ketone)  
Methylene bromide (Dibromomethane)  
Methylene chloride (Dichloromethane)  
Naphthalene  
Propionitrile (Ethyl cyanide)  
Styrene  
Tertiary amyl methyl ether  
Tertiary butyl alcohol  
1,1,1,2-Tetrachloroethane

**TABLE V**

**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

1,1,2,2-Tetrachloroethane  
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene; PCE)  
Toluene  
1,2,4-Trichlorobenzene  
1,1,1 -Trichloroethane, Methylchloroform  
1,1,2-Trichloroethane  
Trichloroethylene (Trichloroethene; TCE)  
Trichlorofluoromethane (CFC- 11)  
1,2,3-Trichloropropane  
Vinyl acetate  
Vinyl chloride (Chloroethene)  
Xylene (total)

**Semi-Volatile Organic Compounds:**

**USEPA Method 8270 - base, neutral, & acid extractables**

Acenaphthene  
Acenaphthylene  
Acetophenone  
2-Acetylaminofluorene (2-AAF)  
Aldrin  
4-Aminobiphenyl  
Anthracene  
Benzo[a]anthracene (Benzanthracene)  
Benzo[b]fluoranthene  
Benzo[k]fluoranthene  
Benzo[g,h,i]perylene  
Benzo[a]pyrene  
Benzyl alcohol  
Bis(2-ethylhexyl) phthalate  
alpha-BHC  
beta-BHC  
delta-BHC  
gamma-BHC (Lindane)  
Bis(2-chloroethoxy)methane  
Bis(2-chloroethyl) ether (Dichloroethyl ether)  
Bis(2-chloro-1-methylethyl) ether (Bis(2-chloroisopropyl) ether; DCIP)  
4-Bromophenyl phenyl ether  
Butyl benzyl phthalate (Benzyl butyl phthalate)  
Chlordane  
p-Chloroaniline  
Chlorobenzilate  
p-Chloro-m-cresol (4-Chloro-3-methylphenol)

**TABLE V**

**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

2-Chloronaphthalene  
2-Chlorophenol  
4-Chlorophenyl phenyl ether  
Chrysene  
o-Cresol (2-methylphenol)  
m-Cresol (3-methylphenol)  
p-Cresol (4-methylphenol)  
4,4'-DDD  
4,4'-DDE  
4,4'-DDT  
Diallate  
Dibenz[a,h]anthracene  
Dibenzofuran  
Di-n-butyl phthalate  
3,3'-Dichlorobenzidine  
2,4-Dichlorophenol  
2,6-Dichlorophenol  
Dieldrin  
Diethyl phthalate  
p-(Dimethylamino)azobenzene  
7,12-Dimethylbenz[a]anthracene  
3,3'-Dimethylbenzidine  
2,4-Dimethylphenol (m-Xylenol)  
Dimethyl phthalate  
m-Dinitrobenzene  
4,6-Dinitro-o-cresol (4,6-Dinitro-2-methylphenol)  
2,4-Dinitrophenol  
2,4-Dinitrotoluene  
2,6-Dinitrotoluene  
Di-n-octyl phthalate  
Diphenylamine  
Endosulfan I  
Endosulfan II  
Endosulfan sulfate  
Endrin  
Endrin aldehyde  
Ethyl methanesulfonate  
Famphur  
Fluoranthene  
Fluorene  
Heptachlor  
Heptachlor epoxide  
Hexachlorobenzene

**TABLE V**

**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

Hexachlorocyclopentadiene  
Hexachloropropene  
Indeno(1,2,3-c,d)pyrene  
Isodrin  
Isophorone  
Isosafrole  
Kepone  
Methapyrilene  
Methoxychlor  
3-Methylcholanthrene  
Methyl methanesulfonate  
2-Methylnaphthalene  
1,4-Naphthoquinone  
1-Naphthylamine  
2-Naphthylamine  
o-Nitroaniline (2-Nitroaniline)  
m-Nitroaniline (3-Nitroaniline)  
p-Nitroaniline (4-Nitroaniline)  
Nitrobenzene  
o-Nitrophenol (2-Nitrophenol)  
p-Nitrophenol (4-Nitrophenol)  
N-Nitrosodi-n-butylamine (Di-n-butylnitrosamine)  
N-Nitrosodiethylamine (Diethylnitrosamine)  
N-Nitrosodimethylamine (Dimethylnitrosamine)  
N-Nitrosodiphenylamine (Diphenylnitrosamine)  
N-Nitrosodipropylamine (N-Nitroso-N-dipropylamine; Di-n-propylnitrosamine)  
N-Nitrosomethylethylamine (Methylethylnitrosamine)  
N-Nitrosopiperidine  
N-Nitrosopyrrolidine  
5-Nitro-o-toluidine  
Pentachlorobenzene  
Pentachloronitrobenzene (PCNB)  
Pentachlorophenol  
Phenacetin  
Phenanthrene  
Phenol  
p-Phenylenediamine  
Polychlorinated biphenyls (PCBs; Aroclors)  
Pronamide  
Pyrene  
Safrole  
1,2,4,5-Tetrachlorobenzene  
2,3,4,6-Tetrachlorophenol

**TABLE V**

**CONSTITUENTS OF CONCERN & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

o-Toluidine  
Toxaphene  
2,4,5-Trichlorophenol  
0,0,0-Triethyl phosphorothioate  
sym-Trinitrobenzene

**Chlorophenoxy Herbicides:**

**USEPA Method 8151**

2,4-D (2,4-Dichlorophenoxyacetic acid)  
Dinoseb (DNBP; 2-sec-Butyl-4,6-dinitrophenol)  
Silvex (2,4,5-Trichlorophenoxypropionic acid; 2,4,5-TP)  
2,4,5-T (2,4,5-Trichlorophenoxyacetic acid)

**Organophosphorus Compounds:**

**USEPA Method 8141**

Atrazine  
Chlorpyrifos  
0,0-Diethyl 0-2-pyrazinyl phosphorothioate (Thionazin)  
Diazinon  
Dimethoate  
Disulfoton  
Ethion  
Methyl parathion (Parathion methyl)  
Parathion  
Phorate  
Simazine